

The following listing of claims will replace all prior versions and listings of claims in the application:

Listing of Claims:

- 1-8. (Canceled)
9. (Previously Presented) An IV pole, comprising:
a base with a set of three or more wheels coupled thereto, wherein the base comprises an enclosure that substantially covers and encloses the set of wheels;
a pole having a lower portion coupled to the base and an upper portion remote from the base;
at least one intravenous fluid reservoir holder proximate the upper portion of the pole;
and
a handle coupled to the pole between the lower portion and the upper portion thereof.
10. (Original) The IV pole of claim 9, further comprising a bumper secured to the enclosure at an outer perimeter thereof.
11. (Original) The IV pole of claim 10, wherein the bumper extends along substantially the entire perimeter of the enclosure.
12. (Original) The IV pole of claim 9, wherein the set of wheels comprises six wheels.
13. (Original) The IV pole of claim 9, further comprising a bumper secured to the base at an outer perimeter thereof.
14. (Original) The IV pole of claim 13, wherein the bumper extends along substantially the entire perimeter of the base.
- 15-16. (Canceled)

17. (Previously Presented) An IV pole, comprising:
a base with a set of three or more wheels coupled thereto;
a pole having a lower portion coupled to the base and an upper portion remote from the base;
at least one intravenous fluid reservoir holder proximate the upper portion of the pole;
and
a handle coupled to the pole between the lower portion and the upper portion thereof,
wherein the handle is movable axially along at least a portion of the pole.

18. (Previously Presented) An IV pole, comprising:
a base with a set of three or more wheels coupled thereto;
a pole having a lower portion coupled to the base and an upper portion remote from the base;
at least one intravenous fluid reservoir holder proximate the upper portion of the pole;
and
a handle coupled to the pole between the lower portion and the upper portion thereof,
wherein the handle comprises a ring oriented obliquely relative to the pole.

19. (Original) The IV pole of claim 18, wherein the handle is movable axially along at least a portion of the pole.

20. (Original) The IV pole of claim 18, wherein the handle further comprises a storage receptacle coupled to the ring.

21-24. (Canceled)

25. (Previously Presented) An IV pole, comprising:
a base with a set of three or more wheels coupled thereto;
a pole having a lower portion coupled to the base and an upper portion remote from the base, wherein the pole comprises a first arm extending substantially vertically upwardly from a first portion of the base and a second arm extending substantially vertically upwardly from a second portion of the base different than the first portion;
at least one intravenous fluid reservoir holder proximate the upper portion of the pole; and
a handle coupled to the pole between the lower portion and the upper portion thereof.
26. (Original) The IV pole of claim 25, wherein an uppermost portion of the first arm is interconnected with an uppermost portion of the second arm via a rigid U-shaped pole section.
27. (Original) The IV pole of claim 25, wherein each of the first and second arms comprises a respective plurality of telescoping tubular sections.
28. (Original) The IV pole of claim 25, wherein each of the first and second arms comprises a lower portion secured to the base, a central portion, and an upper portion.
29. (Original) The IV pole of claim 28, wherein the upper portion of the first arm is interconnected with the upper portion of the second arm.
30. (Original) The IV pole of claim 29, wherein the central portions of the first and second arms are rigidly interconnected via a stabilization bar.
31. (Original) The IV pole of claim 30, wherein the stabilization bar defines a plurality of routing channels sized to receive flexible tubing used to carry intravenous fluid.

32. (Original) An IV pole, comprising:

a base with a set of at least three wheels coupled thereto, wherein the base includes an enclosure that substantially covers the wheels and a bumper secured to the enclosure at an outer perimeter thereof;

a pole comprising first and second arms extending substantially vertically upwardly from the base, each arm comprising respective lower, central, and upper telescoping portions, wherein the respective lower portions of the first and second arms are securely coupled to the base, and wherein the respective upper portions of the first and second arms are rigidly interconnected with one another, and wherein the respective central portions of the first and second arms are rigidly interconnected via a stabilization bar having a plurality of routing channels sized to receive flexible tubing;

at least one intravenous fluid reservoir holder mounted to the pole proximate the uppermost end thereof; and

a handle coupled to the pole and movable axially along at least a portion of the pole, wherein the handle comprises a ring oriented obliquely relative to the pole.